



Gova UG. (haftungsbeschränkt)

Manfred van TRIEL + Peter van TRIEL

Specialist for Special + High Nickel Alloy's // Sales // Marketing

EXTERNAL WAREHOUSE

MATERIAL TO ASTM SPECIFICATION

TESTED IN ACCORDANCE WITH NORSOK THROUGH RULING SECTION

Stock List - October 2025

Bar- Forgings- Pipe

F51	
Dia (mm)	Weight
20	133
25	878
30	3.087
40	752
50	2.173
70	2.242
90	807
95	1.587
100	1.673
101,6	3.942
110	2.720
115	1.488
125	2.036
127	4.097
130	247
135	2.399
139,7	6.458
140	940
150	5.119
155	3.478
165,1	2.800
170	1.819
175	6.541
180	6.617
190	5.209
200	2.450
203,2	2.597
228,6	6.429
230	370
250	5.160
254	3.169
260	6.616
280	3.872
320	9.491
330,2	1.287
355,6	2.856
457,2	440
475	6.588

F53	
Dia (mm)	Weight
20	99
25	1.899
30	1.413
35	2.115
40	1.889
50	3.733
55	1.562
60	369
65	1.203
80	2.223
90	3.357
101,6	4.969
110	934
114,3	5.150
120	393
125	4.289
127	1.014
130	3.606
140	8.247
152,4	1.747
160	4.627
165	4.660
170	3.071
175	1.283
180	6.468
190	16.956
190,5	600
200	10.121
203,2	128
210	2.432
215,9	837
220	3.408
225	1.419
228,6	5.099
240	9.530
250	2.558
254	13.892
279,4	3.213
304,8	26.821
330,2	16.453
355,6	6.153
381	11.798
406,4	9.697
431,8	6.569
457,2	6.692
508	1.298

F55	
Dia (mm)	Weight
25,4	2.747
50,8	6.088
57,15	3.779
63,5	2.877
70	3.996
80	2.779
82,55	265
90	246
101,6	11.403
110	596
114,3	19.104
120	249
130	12.641
133,35	10.171
139,7	15.298
140	1.311
152,4	3.477
165,1	12.500
177,8	13.851
180	2.775
190,5	8.279
203,2	4.855
215,9	2.296
222	10.423
228,6	8.004
241,3	1.650
254	4.137
265	5.620
270	10.508
279,4	8.768
280	5.791
290	8.422
304,8	15.940
355,6	2.836
360	4.745
381	529
406,4	11.068
431,8	8.361
457,2	14.853
482,6	483
560	612

AISI 4140	
Dia (mm)	Weight
25	44
50,8	1.597
50,8	1.023
63,5	7.722
63,5	2.420
70	390
76,2	7.257
88,9	5.321
101,6	4.354
127	12.312
139,7	9.024
152,4	13.747
165,1	6.680
177,8	10.124
180	8.287
190	19.346
203,2	25.361
228,6	13.584
254	6.357

AISI 4145	
Dia (mm)	Weight
31,75	60
50,8	3.846
66	5.270
76,2	4.353
88,9	6.544
101,6	6.132
114,3	3.594
127	9.012
152,4	5.621
158,8	1.468
165,1	15.864
170	26.381
177,8	36.797
184	13.565
190,5	1.624
196,85	476
203,2	18.264
205	8.755
210	1.298
215,9	9.425
222,3	940
228,6	28.973
241,3	7.492
254	7.511
273,1	8.949
279,4	4.770
304,8	4.152
330,2	8.620
355,6	7.503
406,4	1.538
460	603

Super 13% CR (95K)	
Dia (mm)	Weight
63,5	8.143
76,2	10.457
76,2	5.523
88,9	6.174
101,6	21.731
101,6	6.603
114,3	19.069
127	25.047
127	7.688
139,7	5.664
140	8.352
152,4	31.288
152,4	11.346
165,1	10.814
165,1	10.257
177,8	9.683
177,8	11.591
190,5	4.204
190,5	12.909
203,2	5.494
203,2	17.948
216	14.168
216	4.368
220	6.528
220	5.131
225	13.412
225	10.131
228,6	15.872
241,3	18.701
254	3.238
254	1.450

AISI 420	
Dia (mm)	Weight
50,8	4.978
63,5	3.755
76,2	18.304
90	4.562
101,6	2.669
110	2.736
115,7	5.257
127	20.726
141,7	9.308
152,4	15.188
158,75	4.175
165,1	956
177,8	10.100
190,5	24.700
196	2.825
200	546
203,2	5.436
210	14.226
216	12.218
220	5.576
228,6	2.281
241	4.570
254	30.555
260	1.162
304,8	3.682

API6A CRA 718	
Dia (mm)	Weight
25,4	265
31,8	169
38,1	85
41	564
44,45	614
50,8	453
57,2	642
63,5	716
76,2	841
82,55	41
95,25	23
139,7	63
152,4	17

Alloy 625 (60K)	
Dia (mm)	
12	4
15,88	274
20	363
25,4	346
30	587
35,83	628
38,1	209
45,36	662
50,8	1.306
60,33	912
63,5	1.418
70	914
76,2	753
95,25	79
101,6	1.137
130	2.190
150	1.099
152,4	2.054
177,8	2.037

Mit freundlichen Grüßen/ Best Regards

Manfred van Triel

Handy: +49 (0) 172 235 4730