



Gova UG. (haftungsbeschränkt)  
 Manfred van TRIEL + Peter van TRIEL  
 Specialist for Special + High Nickel Alloy's // Sales // Marketing

**EXTERNAL WAREHOUSE**  
 MATERIAL TO ASTM SPECIFICATION  
 TESTED IN ACCORDANCE WITH NORSOK THROUGH RULING SECTION  
 Stock List - February 2026  
 Bar- Forgings- Pipe

F51	
Dia (mm)	Weight
20	133
25	878
30	3,087
40	795
50	2,170
70	2,221
90	945
95	1,531
100	1,617
101.6	3,516
110	2,595
115	1,048
125	1,949
127	3,896
130	213
135	2,367
139.7	6,397
140	7,337
150	5,936
155	3,265
165.1	1,458
170	888
175	6,064
180	3,483
190	4,649
200	2,450
203.2	996
228.6	4,154
230	370
250	1,265
254	1,097
260	4,080
280	3,534
320	9,136
330.2	517
355.6	2,856
457.2	0
475	5,545

F53	
Dia (mm)	Weight
20	160
25	1,899
30	1,248
35	1,993
40	1,770
50	3,682
55	1,401
60	369
65	1,203
80	2,116
90	3,243
101.6	4,361
110	740
114.3	5,236
120	393
125	4,289
127	910
130	6,010
140	10,261
152.4	2,330
160	4,627
165	4,618
170	3,071
175	1,283
180	6,090
190	13,091
190.5	600
200	10,121
203.2	17,617
210	979
215.9	837
220	3,115
225	1,320
228.6	2,248
240	6,825
250	1,901
254	11,261
279.4	7,713
304.8	23,107
330.2	14,223
355.6	6,016
381	11,798
406.4	9,588
431.8	6,257
457.2	6,692
508	381

F55	
Dia (mm)	Weight
25.4	2,747
50.8	6,088
57.15	3,768
63.5	2,877
70	3,967
80	2,566
82.55	59
90	156
101.6	10,196
110	95
114.3	18,523
120	108
130	9,526
133.35	10,060
139.7	11,387
140	319
152.4	3,187
165.1	8,130
177.8	13,586
180	1,355
190.5	6,347
203.2	17,765
215.9	5,799
222	9,471
228.6	5,845
241.3	1,225
254	6,041
265	4,400
270	10,215
279.4	8,768
280	5,327
290	7,761
304.8	11,728
330.2	11,356
355.6	2,264
360	4,519
381	7,015
406.4	8,975
431.8	6,421
457.2	12,196
482.6	329
560	612

AISI 4140	
Dia (mm)	Weight
25	44
50.8	1,575
50.8	1,029
63.5	7,771
63.5	2,435
70	393
76.2	7,267
88.9	3,996
101.6	3,564
127	7,757
139.7	9,081
152.4	11,742
165.1	4,202
177.8	10,188
180	8,340
190	17,584
203.2	24,185
228.6	0
254	6,398

AISI 4145	
Dia (mm)	Weight
31.75	60
50.8	3,871
66	5,264
76.2	4,045
88.9	6,586
101.6	6,172
114.3	1,692
127	9,070
152.4	4,276
158.8	623
165.1	13,781
170	24,768
177.8	24,949
184	26,719
190.5	10,293
196.85	240
203.2	27,749
205	5,701
210	1,306
215.9	9,198
222.3	306
228.6	28,354
241.3	7,181
254	3,184
273.1	9,006
279.4	4,801
304.8	4,178
330.2	10,759
355.6	7,551
406.4	9,170
460	11,748

Super 13% CR (95K/110K)	
Dia (mm)	Weight
63.5 (95K)	8,143
76.2 (95K)	10,457
76.2 (110K)	5,523
88.9 (95K)	6,174
101.6 (95K)	21,731
101.6 (110K)	6,603
114.3 (95K)	19,069
127 (95K)	25,047
127 (110K)	7,688
139.7 (95K)	5,664
140 (110K)	8,352
152.4 (95K)	31,288
152.4 (110K)	11,346
165.1 (95K)	10,814
165.1 (110K)	10,257
177.8 (95K)	9,683
177.8 (110K)	11,591
190.5 (95K)	4,204
190.5 (110K)	12,909
203.2 (95K)	5,494
203.2 (110K)	17,948
216 (95K)	14,168
216 (110K)	4,368
220 (95K)	6,528
220 (110K)	5,131
225 (95K)	13,412
225 (110K)	10,131
228.6 (110K)	15,872
241.3 (110K)	18,701
254 (110K)	3,238
254 (95K)	1,450

AISI 420	
Dia (mm)	Weight
50.8	4,946
63.5	3,436
76.2	16,717
90	4,533
101.6	691
110	2,718
115.7	3,749
127	13,254
141.7	9,249
152.4	14,703
158.75	2,609
165.1	333
177.8	7,505
190.5	23,416
196	1,872
200	488
203.2	4,274
210	14,134
216	11,645
220	3,242
228.6	1,910
241	3,891
254	21,600
260	1,154
304.8	2,445

API6A CRA 718 (120K)	
Dia (mm)	Weight
25.4	266
31.8	169
38.1	85
41	564
44.45	614
50.8	453
57.2	642
63.5	716
76.2	841
82.55	41
95.25	23
139.7	63
152.4	17

Alloy 625 (60K)	
Dia (mm)	Weight
12	4
15.88	274
20	363
25.4	346
30	587
35.83	628
38.1	209
45.36	662
50.8	1,306
60.33	912
63.5	1,418
70	914
76.2	753
95.25	79
101.6	1,137
130	2,190
150	1,099
152.4	2,054
177.8	2,037

Mit freundlichen Grüßen/ Best Regards  
 Manfred van Triel  
 Handy: +49 (0) 172 235 4730  
 Mail: mp-stainless@outlook.com