



Gova UG. (haftungsbeschränkt)

Manfred van TRIEL + Peter van TRIEL

Specialist for Special + High Nickel Alloy's // Sales // Marketing

EXTERNAL WAREHOUSE

MATERIAL TO ASTM SPECIFICATION

TESTED IN ACCORDANCE WITH NORSOK THROUGH RULING SECTION

Stock List - October 2026

Bar- Forgings- Pipe

F51	
Dia (mm)	Weight
20	123
25	831
30	3.046
40	474
50	1.592
70	903
75	29
90	49
95	1.565
100	1.617
101.6	1.629
110	2.216
115	60
125	0
127	3.503
130	75
135	1.180
139.7	6.320
140	940
150	4.491
155	1.533
165.1	0
170	0
175	5.104
180	0
190	4.181
200	49
210	0
228.6	2.291
230	111
250	317
254	315
260	1.606
280	1.643
320	8.098
330.2	250
355.6	0
457.2	0
475	530

F53	
Dia (mm)	Weight
20	162
25	1.891
30	1.098
35	1.722
40	1.149
50	3.670
55	1.409
60	369
65	1.148
80	2.022
90	40
101.6	3.866
110	632
114.3	5.120
115	86
120	393
125	2.644
127	890
130	5.523
140	9.895
152.4	667
155	34
160	4.627
165	4.224
170	3.071
175	1.283
180	6.090
190	11.698
190.5	934
200	10.107
203.2	60
205	13.372
210	7.309
215.9	170
220	3.115
225	1.303
228.6	2.248
240	946
250	0
254	1.851
279.4	4.853
304.8	15.986
330.2	3.171
355.6	4.889
381	9.070
406.4	9.403
431.8	6.205
457.2	6.082

F55	
Dia (mm)	Weight
12.7	4
25.4	2.516
38.1	13
50	7
50.8	0
57.15	3.850
60	16
63.5	2.614
70	38
80	435
82.55	0
90	0
101.6	420
110	0
114.3	10.926
120	31
130	1.610
133.35	7.134
139.7	9.253
140	151
152.4	0
165.1	332
177.8	10.523
180	1.280
190.5	874
203.2	462
205	1.010
215.9	2.848
222	8.173
228.6	2.784
241.3	94
254	5.039
265	713
270	10.226
279.4	3.781
280	3.843
290	2.748
304.8	1.325
330.2	2.575
355.6	332
360	4.519
381	6.211
406.4	4.085
431.8	3.553
457.2	11.212
482.6	0

AISI 4140	
Dia (mm)	Weight
25	29
50.8	89
50.8	416
50.8	986
63.5	3.743
63.5	2.530
70	242
76.2	9.881
88.9	5.761
101.6	5.428
127	4.995
139.7	0
152.4	10.547
165.1	11.952
177.8	8.186
180	7.490
190	13.127
203.2	22.729
215.9	14.265
228.6	6.412
254	0

AISI 4145	
Dia (mm)	Weight
50.8	1.495
66	3.662
76.2	0
88.9	5.718
101.6	3.816
114.3	7.830
127	5.558
140	2.666
152.4	6.783
158.8	669
165.1	15.493
170	24.840
177.8	11.129
184	17.590
190.5	3.300
196.85	0
203.2	12.164
205	45.190
210	1.140
215.9	578
222.3	548
228.6	12.100
241.3	5.600
254	1.424
273.1	6.170
279.4	1.492
304.8	3.682
330.2	142
355.6	6.599
406.4	1.007
460	210

Super 13% CR (95K/110K)	
Dia (mm)	Weight
63.5 (95K)	8.142
76.2 (95K)	10.187
76.2 (110K)	2.151
88.9 (95K)	16.082
101.6 (95K)	20.845
101.6 (110K)	6.271
114.3 (95K)	25.063
127 (95K)	23.442
127 (110K)	5.192
139.7 (95K)	5.902
140 (110K)	7.343
152.4 (95K)	30.778
152.4 (110K)	2.118
165.1 (95K)	9.860
165.1 (110K)	8.275
177.8 (95K)	9.682
177.8 (110K)	1.473
190.5 (95K)	4.204
190.5 (110K)	3.953
203.2 (95K)	3.207
203.2 (110K)	2.815
216 (95K)	6.229
216 (110K)	735
220 (95K)	2.553
220 (110K)	86
225 (95K)	11.086
225 (110K)	4.237
228.6 (110K)	10.179
241.3 (110K)	15.359
254 (110K)	2.631
254 (95K)	1.450
280 (110K)	3.901

AISI 420	
Dia (mm)	Weight
50.8	4.012
63.5	1.856
76.2	8.872
90	3.933
101.6	3.335
110	0
115.7	13.917
127	17.106
141.7	6.808
152.4	6.091
158.75	2.050
165.1	1.057
177.8	8.301
190.5	17.743
196	2.695
200	1.365
203.2	1.648
210	13.990
216	5.828
220	2.564
228.6	4.370
241	3.548
254	18.195
260	1.011
304.8	2.335

Mit freundlichen Grüßen/ Best Regards

Manfred van Triel

Handy: +49 (0) 172 235 4730

Mail: mp-stainless@outlook.com